



## DL-K 16-130/T-EN54

- UV-resistant
- elegant design
- BS 5839



EN 54-24:2008  
**Ref. Nr.:** 005-13  
**ID-Code:** SAA-LS05  
 1438-CPD-0325

ic audio GmbH, Boehringerstraße 14a,  
 D-68307 Mannheim, Germany

CE-Symbol gemäß Richtlinie 93/68EWG

### Technical Data (Electrical)

| Description                | DL-K 16-130/T-EN54 |
|----------------------------|--------------------|
| Power                      | 16/8/4 W           |
| Impedance (100V)           | 625/1250/2500 ohm  |
| Frequency Range            | 130 - 13.300 Hz    |
| Frequency Response         | 130 - 23.500 Hz    |
| SPL IEC268-5, 1W/1m        | 85,0 dB            |
| SPL EN54-24, Pmax/4m       | 86,5 dB            |
| Sensitivity EN54-24, 1W/4m | 73,0 dB            |
| Sensitivity EN54-24, 1W/1m | 85,0 dB            |
| Dispersion -6dB, 500Hz     | h/v 360°           |
| Dispersion -6dB, 1KHz      | h/v 196°           |
| Dispersion -6dB, 2KHz      | h/v 132°           |

Dispersion -6dB, 4KHz      h/v 171 °

Please note: Because of many different types of ceiling materials and ceiling strengths we recommend to build in a sample of the speaker to match the requirements accurately.



## Technical Data (Mechanical)


|                       |                   |
|-----------------------|-------------------|
| Dimensions            | 185x157 mm        |
| IP Rating             | IP35              |
| Weight (net)          | 1,50 kg           |
| Temperature range     | -10 / +55 C°      |
| Mounting              | Mounting hook     |
| Connector             | ceramic block     |
| Terminal diameter     | 3,2 mm            |
| Maximum cable passage | 8 mm <sup>2</sup> |
| Colour                | RAL 9010          |

## Product Attributes




## Technical Diagrams








## Frequency Response Diagrams




## Polar Diagrams














ic audio loudspeakers are tested and classified according to the IEC standard 60529 (degree of protection by enclosure) against the penetration of foreign objects and moisture. The classification is conforming to standards through characterization with a fixed code. This code consists of the letters IP (International Protection) followed by two digits. The first digit indicates the degree of protection against dust and the second digit the degree of protection against water. Please note that the testing of the products has been carried out in laboratory conditions which are not always 100% comparable with the conditions of different installation environments. This protection can be reduced due to normal wear and tear depending on the installation environment.

RoHS compliant (2011/65/EU)

The IP rating specified is based on ic audio test results, not on CNBOP-PIB test results. Certification only verifies the minimum requirements for EN54-24 compliance.

**Article Nr.: 20122605**

**Packing Unit: 6**

