

DK 6/T

- high sound pressure level
- weather proof
- also be used as in-wall speaker



The 6W powered speaker is equipped with a 100V line transformer with 4 power adjustments, also low-impedance operation (8ohm) is possible. The compact, impact-resistant ABS housing UL94V0 in RAL 7035 guarantees long-term stability. The speaker is secured with the high protection class IP 67 against the security risks of environmental influences.

Included is a aluminium mounting bracket for easy installation. The speaker is connected by a 6-pin connection cable with 1 meter length.

ic audio GmbH • Boehringerstraße 14a • D-68307 Mannheim • Germany
Fon: ++49 (0) 621 / 77096 -0 • Fax: ++49 (0) 621 / 77096 -26 • Email: info@ic-audio.com

Status: 2022-11-08

Technical Data

Description	DK 6/T
Power	6/3/1,5/0,75 (8) W
Frequency Range	883 - 7.500 Hz
Frequency Response	500 - 9.500 Hz
SPL 1W/1m, peak	110 dB
SPL Pmax/1m, peak	117,8 dB
Sensitivity 1W/1m	106,2 dB
Dispersion (-10dB)	360° (h) / 360° (v)
Temperature range	-20 / +90 °C
Dimensions	143x110 mm
Weight (net)	1,00 kg
Colour	RAL 9016
Connector	6-pin cable
Mounting	Aluminium bracket
Packing Unit	12
IP Rating	IP67


Product Attributes



ic audio GmbH • Boehringerstraße 14a • D-68307 Mannheim • Germany
Fon: ++49 (0) 621 / 77096 -0 • Fax: ++49 (0) 621 / 77096 -26 • Email: info@ic-audio.com


Status: 2022-11-08

Polar Diagrams




ic audio GmbH • Boehringerstraße 14a • D-68307 Mannheim • Germany
Fon: ++49 (0) 621 / 77096 -0 • Fax: ++49 (0) 621 / 77096 -26 • Email: info@ic-audio.com

Frequency Response Diagrams



ic audio GmbH • Boehringerstraße 14a • D-68307 Mannheim • Germany
Fon: ++49 (0) 621 / 77096 -0 • Fax: ++49 (0) 621 / 77096 -26 • Email: info@ic-audio.com

Technical Diagrams



RoHS compliant (2011/65/EU)

Article Nr.:
20071042

Packing Unit:
12

ic audio GmbH • Boehringerstraße 14a • D-68307 Mannheim • Germany
Fon: ++49 (0) 621 / 77096 -0 • Fax: ++49 (0) 621 / 77096 -26 • Email: info@ic-audio.com

Status: 2022-11-08