



NET-5 DL-BR 165

- Live, recorded or scheduled Messages
- Multicast group paging with paging prioritization
- Speech generator for announcements



Get rid of cost increasing 100V-cabling and stacked amplification. Be flexible with centrally managed and remotely controlled network speakers. The 2-way bassreflex ceiling speaker NET-5 DL-BR 165 is equipped with an 15W internal amplifier. The PoE-powered speaker is compatible with an universal POE-switch.

Each speaker is addressable and capable of playing clear audio from a multicast source. Stream your live, recorded or scheduled messages to single speakers or speaker groups. Simple and easy mounting of the speaker is done by screws.

NET-5 CONTROL enables a load of dedicated features such as music playback and voice messages simultaneously broadcasted, configuration of 1200 speaker groups, paging prioritization, adjustable volume for each speaker, custom playlists and scheduled broadcasts, text to speech generator, and much more.

If you don't like to use a headset for announcements you can choose the desktop paging microphone NET-5 CALL.

Technical Data

Description	NET-5 DL-BR 165
Power	15 W
Dimensions	250 x 175 mm
Weight (net)	2,60 kg
Colour	RAL 9010
Packing Unit	4
Ceiling Cut-out	222 mm
Impedance	4-16 Ohm
Power Input	PoE 802.3af or PoE 802.3at & DC 12V
Bitrate	8000 - 512 kbit/s
Samplerate	8000 - 48 kbit/s
Audio Format	MP3
Supported Protocols	ARP, TC/IP, UDP, ICMP & IGMP
Audio Quality	16 Bit
Network I/F	10/100 Mb/s

Product Attributes



RoHS compliant (2011/65/EU)



Article Nr.:
20206215

Packing Unit:
4

