

DL-FF 06-130/T

- Built-in dome for concrete ceilings
- Grille with rotary fixing
- 70mm built-in depth



The 6W in-ceiling loudspeaker is equipped with a 130 mm full-range loudspeaker and a 100V transformer with 3 power adjustments. The powder-coated metal housing similar to RAL 9010 guarantees lasting stability and a flawless appearance.

A Wieland plug ensures a fast and uncomplicated connection. The loudspeaker is impregnated against humidity and protected against environmental influences with protection class IP 21.

Strong stability is provided by 12 screws at the front. The connection cables can be connected via a cable gland (PG9).

This loudspeaker is also suitable for installation in concrete ceilings.

ic audio GmbH • Boehringerstraße 14a • D-68307 Mannheim • Germany
Fon: ++49 (0) 621 / 77096 -0 • Fax: ++49 (0) 621 / 77096 -26 • Email: info@ic-audio.com

Technical Data


Description	DL-FF 06-130/T
Power	6/3/1,5 W
Frequency Range	200-16.000 Hz
SPL 1W/1m	92,0 dB
SPL 1W/1m, peak	101,5 dB
Dispersion (-10dB)	180°
Temperature range	-20 / +80 °C
Dimensions	161,5x 78 mm
Weight (net)	1,20 kg
Colour	similar to RAL 9010
Connector	0,5 m connection cable, colour white;1 x male connector Wieland, GST18/3S S1 ZR1 WS
Mounting	Screws
Packing Unit	12
Material	Metal
Ceiling Cut-out	144 mm (+/- 1mm)

Product Attributes




ic audio GmbH • Boehringerstraße 14a • D-68307 Mannheim • Germany
Fon: ++49 (0) 621 / 77096 -0 • Fax: ++49 (0) 621 / 77096 -26 • Email: info@ic-audio.com

Frequency Response Diagrams



Technical Diagrams



RoHS compliant (2011/65/EU)

Article Nr.:
20122571

Packing Unit:
12

ic audio GmbH • Boehringerstraße 14a • D-68307 Mannheim • Germany
Fon: ++49 (0) 621 / 77096 -0 • Fax: ++49 (0) 621 / 77096 -26 • Email: info@ic-audio.com