



AMP 4x120

- 24V emergency power supply
- 4 channels
- 230V and 115V operation

The 4-channel power amplifier AMP 4 x 120 is specially designed for the application in public buildings, schools or coliseums.

The amplifier with 4 x 120 Watt is protected against overload and short circuit. A fan provides for thermal stability. The output level is shown by a LEDVU meter. With the speaker outputs of 70 Volt, 100 Volt and 8 Ohm the AMP 4 x 120 can be recommended for all kinds of installation condition.

1x XLR, 1 x 1/4 inch jack and 2 x cinch connectors for incoming signals are available for each channel. The 19-inch housing (3U) allows for space-saving mounting in racks.

Technical Data

Description	AMP 4x120
Power (Max/Rated)	4 x 120 W
Inputs	Line input: 1V, 47Kohm symmetrisch, unsymmetrisch, balanced, unbalanced
Frequency response	50Hz 50~20KHz $\hat{A} \pm 3$ dB
Outputs	8ohm, 100V (70V/100V selectable)
THD	Less than 1% at 1 KHz, rated power
Mains/Battery Voltage	AC 230V/240V 50/60Hz DC 24V (MAX 10% deviation)
Power consumption	1100 W
Colour	black
Dimensions	133x483x380 mm
Weight (net)	25,70 kg
Packing Unit	1
24 volt	

Product Attributes



Measurements according to DIN IEC 268-5



Article Nr.:
80000050

Packing Unit:
1

