



PRO 150-200/T plus black-EN54

- Outdoor application
- Strong beam type sound
- IP 66



EN 54-24:2008
Ref. Nr.: 021-09
ID-Code: SAA-LS26
 1438-CPR-0814

ic audio GmbH, Boehringerstraße 14a,
 D-68307 Mannheim, Germany

CE-Symbol gemäß Richtlinie 93/68EWG

Technical Data (Electrical)

Description	PRO 150-200/T plus black-EN54
Power	150/75/38W (8ohm)
Impedance (100V)	67/133/263 ohm
Frequency Range	90 - 19.000 Hz
Frequency Response	75 - 20.000 Hz
SPL IEC268-5, 1W/1m	98,0 dB
SPL EN54-24, Pmax/4m	102,5 dB
Sensitivity EN54-24, 1W/4m	84,7 dB
Dispersion -6dB, 500Hz	170° (h) 180° (v)
Dispersion -6dB, 1KHz	79° (h) 80° (v)

Dispersion -6dB, 2KHz	50° (h) 62° (v)
-----------------------	--------------------

Dispersion -6dB, 4KHz	85° (h) 70° (v)
-----------------------	--------------------

Technical Data (Mechanical)

Dimensions	315x305x350 mm
------------	----------------

IP Rating	IP66
-----------	------

Weight (net)	11,85 kg
--------------	----------

Temperature range	-25 / +70 °C
-------------------	--------------

Mounting	Mounting bracket
----------	------------------

Connector	4-pin screw terminal
-----------	----------------------

Terminal diameter	2,5 mm
-------------------	--------



Maximum cable passage	4,9 mm ²
-----------------------	---------------------



Colour	black
--------	-------

Product Attributes




Technical Diagrams








Frequency Response Diagrams





Polar Diagrams











ic audio loudspeakers are tested and classified according to the IEC standard 60529 (degree of protection by enclosure) against the penetration of foreign objects and moisture. The classification is conforming to standards through characterization with a fixed code. This code consists of the letters IP (International Protection) followed by two digits. The first digit indicates the degree of protection against dust and the second digit the degree of protection against water. Please note that the testing of the products has been carried out in laboratory conditions which are not always 100% comparable with the conditions of different installation environments. This protection can be reduced due to normal wear and tear depending on the installation environment.

RoHS compliant (2011/65/EU)

The IP rating specified is based on ic audio test results, not on CNBOP-PIB test results. Certification only verifies the minimum requirements for EN54-24 compliance.

Article Nr.: 20217063

Packing Unit: 1

